

# REPLACEMENT PARTS GUIDE

## 5039D Tractor (TREM IIIA Engine) (Worldwide Edition)



### HYDRAULIC



#### FILTER ELEMENT [RE45864](#) (MITA)

[SJ11062](#) (USE WITH  
JOHN DEERE ROCK-  
SHAFT)

Replace after initial 100 hours and change every 500 hours and every 1250 hours.

### ENGINE



#### OIL FILTER [RE507204](#) (For India) [T19044](#) (For Export)

Change every 100 hours and 250 hours.



#### PRIMARY AIR FILTER [RE68048](#) SECONDARY AIR FILTER [RE68049](#)



Change after every 250 hours or annually which ever comes first. Change required.



#### PRIMARY FUEL FILTER [RE508953](#) FINAL FILTER [RE508954](#)



Replace after every 500 hours.



**JOHN DEERE**  
Genuine Parts and Service

# CAPACITIES

## 5039D Tractor (TREM IIIA Engine) (Worldwide Edition)

**CAPACITIES (Approximate):**

**Fuel Tank:**

..... 60 L (13.19 gal)

**Crankcase including Filter Change:  
Plus-50™**

..... 8.5 L (1.86 gal)

**Transmission and Hydraulic System:  
Hy-Gard™**

Oil Axle ..... 32 L (7.03 gal)


Grease Axle ..... 30 L (6.56 gal)





# REPLACEMENT PARTS GUIDE


## 5039D Tractor (TREM IIIA Engine) (Worldwide Edition)

### ENGINE

 **BRAKE DISK**  
[SJ18396](#) (2100 RPM)  
(W/ HANDBRAKE)


 **ALTERNATOR**  
[RE258846](#) (ALTERNATOR, 40 A)

 **CLUTCH DISK**  
[SJ29350](#) (TRACTION)  
[RE242274](#) (PTO)


 **FAN BELT DRIVE**  
[SU63793](#) (LGTH = 1340 mm)



### CAB

 **SEAT**  
[SJ34660](#) (POWER STEERING)  
[RE73192](#) (BOTTOM)  
[RE212692](#) (BACK)

### AXLE

 **TIE ROD**  
[R225906](#) (W/ SCV)  
[RE190506](#) (RH) (2WD)  
[RE190481](#) (LH) (2WD)  
[RE192255](#) (TIE ROD ASSEMBLY)  
(2WD)